


Flexible Assembly Systems

Chairs: Daniel Cox, M. A. Erdmann

Uncertainty Reduction Using Dynamics

M. Moll and M. A. Erdmann
Carnegie Mellon University

- For assembly tasks parts often have to be oriented before they can be put in an assembly. The results presented in this paper are a component of the automated design of parts orienting devices.
- We optimize the shape of the support surface and drop height that minimize the entropy of the pose distribution of a part. We use dynamic simulation in combination with quasi-capture regions to quickly compute the pose distribution.
- Our simulation and experimental results confirm that our dynamic simulator can be used to find the true pose distribution of an object.
- This new approach is a feasible way to assist in the design of parts orienting devices.



Flexible Robot-Assembly Using a Multi-Sensory Approach

Stefan Joerg¹, Joerg Langwald¹, Johannes Stelter¹, Gerd Hirzinger¹
and Ciro Natale²

¹German Aerospace Center and ²Università degli Studi di Napoli Federico II


- Integrated Assembly Cell for flexible Robot-Assembly on moving parts
- Model-based real-time vision system for 3 D Pose Estimation and Tracking, force control using innovative compliant 6 DOF F/T sensor, automatic force controller design
- The system's robustness was demonstrated with great success at the KUKA booth during the Hannover Fair 1999
- Complex assembly problems can be solved with sensor-controlled robots.



A Component-Based Approach to the Holonic Control of a Robot Assembly Cell

Jin-Lung Chirn and Duncan C. McFarlane
University of Cambridge


- reconfigurable manufacturing control architecture to long-term changes
- component-based development and holonic manufacturing systems
- execution control systems for a robot assembly cell
- implementation of plug-and-play manufacturing control



Flexible Handling in Disassembly with Screw nail Indentation

B. R. Zuo, A. Stenzel and G. Seliger
Technical University Berlin


- Flexible handling in disassembly
- Generate new surfaces with a screw nail to transmit the forces and torque's
- Development and validation of a mathematical model to calculate the indentation torque for the screw nail
- Realizable and cost-effective solution for handling in disassembly



A system for automatic assembly and disassembly operations

Swee M. Mok¹, Chi-haur Wu² and D. T. Lee³

¹Motorola Inc., ²Northwestern University and ³Academia Sinica



Automatic Object Recognition as Part of an Integrated Supervisory Control System

T. Tuytelaars, A. Zaatri, Luc Van Gool and H. Van Brussel
University of Leuven

- Easy interaction with objects under tele-operation
- through an automatic object recognition module
- viewpoint & illumination invariant
- integrated in a robust ISCS with different control levels, error recovery, anticipation, ...

